

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.

(12)

# **EUROPEAN PATENT APPLICATION**

(21) Application number: 87307990.9

(51) Int. Cl.<sup>4</sup>: H 01 R 23/68

(22) Date of filing: 10.09.87

(30) Priority: 10.09.86 JP 211491/86  
 10.09.86 JP 211493/86  
 17.09.86 JP 219060/86  
 30.01.87 JP 18652/87  
 26.02.87 JP 43947/87  
 26.02.87 JP 43948/87  
 03.03.87 JP 46766/87  
 09.03.87 JP 52173/87  
 15.05.87 JP 71774/87  
 04.06.87 JP 138936/87  
 18.06.87 JP 150228/87

(43) Date of publication of application:  
 16.03.88 Bulletin 88/11

(84) Designated Contracting States: DE GB

(71) Applicant: THE FURUKAWA ELECTRIC CO., LTD.  
 6-1, 2-chome, Marunouchi Chiyoda-ku  
 Tokyo (JP)

(72) Inventor: Hikami, Toshiya Hiratsuka Works  
 Furukawa El.Co. Ltd. 9, Higashi-Hachiman 5-chome 1  
 Hiratsuka-shi Kanagawa-ken (JP)

Yoshida, Koji Hiratsuka-Works  
 Furukawa El.Co. Ltd. 9, Higashi-Hachiman 5-chome 1  
 Hiratsuka-shi Kanagawa-ken (JP)


Obara, Yuichi Hiratsuka Works  
 Furukawa El.Co. Ltd. 9, Higashi-Hachiman 5-chome 1  
 Hiratsuka-shi Kanagawa-ken (JP)

Fuse, Kenichi Hiratsuka Works  
 Furukawa El.Co. Ltd. 9, Higashi-Hachiman 5-chome 1  
 Hiratsuka-shi Kanagawa-ken (JP)

(74) Representative: Gibson, Stewart Harry et al  
 Urquhart-Dykes & Lord Midsummer House 419B  
 Midsummer Boulevard  
 Central Milton Keynes, MK9 3BN (GB)

(54) Electronic connector.

(57) An electronic connector which has a plurality of contacts associated in one or more rows in a connector housing, a shape memory spring associated in the connector housing for driving the contacts, the shape memory spring transmitting a recovery force generated when the shape memory spring reaches its transformation temperature or higher to the contacts while recovering the shape stored when the shape memory spring reaches its transformation temperature or higher and returning to the shape before the shape memory recovery by the spring force of the contact when the shape memory spring reaches below its transformation temperature. Thus, the electronic connector can mount or dismount contacts at each other without inserting or removing force or substantially without inserting or removing force in a simple structure with less number of parts.



## Description

## ELECTRONIC CONNECTOR

This invention relates to an electronic connector capable of inserting or removing an opposite contact in the state near a low inserting or removing force or without inserting or removing force in combination with a shape memory spring as an actuator of the contact.

Recently, as integrated circuits (such as ICs, LSIs) have progressed, electronic devices and equipments are further enhanced in density and are developed in multifunctions. Thus, the pitch of the contacts of connectors has been narrowed, and the number of the contacts has been increased. Here, indispensable problems arise in which inserting and removing forces of electronic parts or circuit boards have been increased at the time of inserting and removing these parts and boards as the contacts have been increased so that unreasonable forces must be exerted. In other words, even if the inserting and removing forces of a pair of contacts are more or less several tens g., when the number of the contacts increases to several hundreds and further several thousands, the inserting and removing forces have arrived at several kg. to several tens kg. In this case, when the components and the boards are inserted or removed by the unreasonable forces, the terminals of the circuit board to be inserted or the circuit board itself is deformed, damaged or causes the contacting portion of the contact of the connector side to be damage or to be, in the worst case, broken.

In order to solve the above-mentioned problems and hence to reduce the inserting and removing forces of the components or the circuit boards, an electronic connector of noninserting and nonremoving force type associated with a shape memory spring as an actuator of a contact has been proposed (as in U.S. Patent Application No. 797652 filed November 13, 1985).

However, since the conventional electronic connector has ordinarily employed a spring as a bias spring or a cam mechanism, its structure is complicated and number of parts is increased so that there arise problems in high density and low cost.

Accordingly, an object of this invention is to provide an electronic connector which can eliminate the above-described problems and drawbacks and which can mount or dismount contacts at each other without inserting or removing force or substantially without inserting or removing force in a simple structure with less number of parts.

In order to achieve the above and other objects, there is provided according to this invention an electronic connector comprising a plurality of contacts associated in a row in a connector housing, a shape memory spring associated in the connector housing for driving the contacts, the shape memory spring transmitting a recovery force generated when the shape memory spring reaches its transformation temperature or higher to the contacts while recovering the shape stored when the shape memory spring

reaches its transformation temperature or higher and returning to the shape before the shape memory recovery by the spring force of the contact when the shape memory spring reaches below its transformation temperature.

The above and other related objects and features of the invention will be apparent from a reading of the following description of the disclosure found in the accompanying drawings and the novelty thereof pointed out in the appended claims.

Fig. 1 is a perspective view showing a first embodiment of an electronic connector according to the present invention;

Fig. 2 is a cross-sectional view of the first embodiment;

Fig. 3 is a perspective view showing an example of a contact of the first embodiment;

Figs. 4 and 5 are explanatory views showing the operating state of the first embodiment;

Figs. 6 and 7 are cross-sectional views showing an applied example of the first embodiment;

Figs. 8 and 9 are partial perspective views of a shape memory spring used in another applied example of the first embodiment;

Fig. 10 is a perspective view showing a second embodiment of an electronic connector according to the present invention;

Figs. 11 and 12 are explanatory views showing the operating state of the second embodiment;

Fig. 13 is a cross-sectional view showing a third embodiment of an electronic connector according to the present invention;

Fig. 14 is a cross-sectional view of an essential portion of a fourth embodiment of an electronic connector of the present invention;

Fig. 15 is a cross-sectional view of an essential portion showing an applied example of the fourth embodiment;

Figs. 16 and 17 are perspective views showing the mounting method of a mounting member of Fig. 15;

Fig. 18 is a perspective view showing another example of the mounting member;

Fig. 19 is a cross-sectional view showing a fifth embodiment of an electronic connector of the present invention;

Fig. 20 is a cross-sectional view showing a sixth embodiment of an electronic connector of the invention;

Figs. 21 and 22 are explanatory views showing the operating state of the sixth embodiment;

Fig. 23 is an enlarged view of an essential portion of a modified example of the sixth embodiment;

Fig. 24 is a perspective view showing a seventh embodiment of an electronic connector of the invention;

Fig. 25 is a perspective view of a stopper

member shown in Fig. 24;

Figs. 26 and 27 are explanatory views showing the operating state of the seventh embodiment;

Fig. 28 is a cross-sectional view showing an eighth embodiment of an electronic connector of the invention;

Fig. 29 is a front view of a contact used in the eighth embodiment;

Fig. 30 is a front view of a contact used in an applied example of the eighth embodiment;

Figs. 31 and 32 are explanatory views showing the operating state of the case that the contact shown in Fig. 30 is used;

Figs. 33 and 34 are cross-sectional views of an essential portion showing the operating state of a ninth embodiment of an electronic connector of the invention;

Figs. 35 and 37 are explanatory views showing the spring force generating state of the contact in the ninth embodiment;

Fig. 38 is a cross-sectional view showing an essential portion showing a tenth embodiment of an electronic connector of the invention;

Fig. 39 is a plan view of an essential portion of the tenth embodiment;

Fig. 40 is a perspective view of a contact of the tenth embodiment;

Fig. 41 is a plan view of an essential portion showing an applied example of the tenth embodiment;

Fig. 42 is a perspective view of the contact of the tenth embodiment; and

Fig. 43 is a perspective view showing eleventh embodiment of an electronic connector of the invention.

Embodiments of an electronic connector according to the present invention will be described in detail with reference to the accompanying drawings.

Figs. 1 to 3 show a first embodiment of an electronic connector of the present invention. As shown in Figs. 1 to 3, the electronic connector of the first embodiment comprises a connector housing 1 made of an insulating material. The connector housing 1 has two rows of contact containing chambers 2 opened at its front surface. A plurality of contacts 3 are contained longitudinally in a row in an aligned state in each contact containing chamber 2 in such a manner that legs 3A of the respective contacts 3 pass externally through the bottom of the connector housing 1. Each contact 3 has a contact base portion 3P and a contact spring portion 3C formed substantially in U-shape to the contact base portion 3P. A shape memory spring holding portion 3D is formed, as shown in Fig. 3, by notching in a tongue shape and erecting the tongue-shaped portion at the intermediate of the contact spring portion 3C. Thus, one end of a shape memory spring 5 to be described later is inserted into the shape memory spring holding portion 3D of the contact 3 to couple the shape memory spring 5 to the shape memory spring holding portion 3D. The shape memory springs 5 are respectively individually provided at the contacts 3 to be disposed to individually drive the contacts 3. The shape memory

spring 5 is formed, for example, of nickel (Ni)-titanium (Ti) alloy or the like, and is formed in U-shaped or V-shaped cross section. Each shape memory spring 5 is inserted at its one end into the shape memory spring holding portion 3D of the contact spring portion 3C to be connected as described above, and is supported at its other end to the central partition portion 1B of the connector housing 1 by a cantilever clamp 40. Reference numeral 7 designates a panellike heater mounted on the surface of the partition portion 1B of the connector housing 1 for heating the shape memory spring 5.

In the embodiment described above, the transformation temperature of the shape memory spring 5 is set to 80°C. Accordingly, the shape memory spring 5 remains the martensitic phase at ambient temperatures to be soft and to be apparently readily plastically deformed. When the shape memory spring 5 is heated to 80°C or higher, the shape memory spring 5 is transformed into the austenitic phase to recover the shape stored in advance, thereby generating a large force at this time.

Figs. 4 and 5 show the operating state of the first embodiment. When the heater 7 is energized to heat the shape memory spring 5 to 80°C or higher, the shape memory spring 5 in the austenitic phase recovers the shape stored in advance (in this case, the shape memory spring stores the shape to close both the edges thereof) as shown in Fig. 4 so that the force generated at this time overcomes the spring force of the contact spring portion 3C to pull the contact spring portion 3C. In other words, the contact base portion 3P and the contact spring portion 3C are separated therebetween. In this state an opposite contact 10 can be inserted or removed without an inserting force or removing force. When the heater 7 is then deenergized to lower the temperature of the shape memory spring 5 to ambient temperatures, the shape memory spring 5 in the martensitic phase becomes soft. As a result, as shown in Fig. 5, the spring force of the contact spring portion 3C overcomes that of the shape memory spring 5 to narrow between the contact base portion 3P and the contact spring portion 3C therebetween, thereby holding the opposite contact 10 therebetween by a predetermined spring force.

When the shape memory spring 5 is heated contrary to the above operation of this embodiment, both the edges of the shape memory spring 5 can be set to open. In this case, the spring force of the contact spring portion 3C overcomes that of the shape memory spring 5 at the ambient temperatures to press the shape memory spring 5 to the partition portion 1B side as shown in Fig. 4. Since the interval between the contact base portion 3P and the contact spring portion 3C is wide at this time, the opposite contact 10 can be inserted into or removed from therebetween without inserting force or removing force. When the shape memory spring 5 is then heated by the heater 7 to 80°C or higher, the shape memory spring 5 recovers the shape stored in advance (in this case, the shape memory spring 5 stores the shape expanding at both edge thereof) as shown in Fig. 5 to press the contact spring portion 3C by the recovery force generated in this case to

the opposite contact 10 by a predetermined contacting pressure. In this case, the shape memory spring holding portion 3D may not be provided.

Applied examples of this first embodiment is shown in Figs. 6 and 7. In the applied examples, the contacts 3 and the shape memory spring 5 are constructed the same as those of the first embodiment except that the shapes of the contact 3 and the shape memory spring 5 are different from those of the first embodiment. In these two applied examples, the shape memory springs 5 are set to the state that the shape memory springs 5 are all noninserting force or nonremoving force state at ambient temperatures.

When the shape memory spring 5 is heated in this state, the shape memory spring recovers the stored shape and simultaneously pushes the contact spring 3C to press the contact spring portion 3C to the opposite contact 10.

In the first embodiment shown in Fig. 1, the shape memory springs 5 are respectively individually provided at the contacts 3. Thus, there arise problems that the number of parts increases, and the forces of the shape memory springs 5 affecting the contacts 3 do not become constant. To solve the problems, the shape memory spring 5 and the contact 3 are insulated therebetween by an insulating material, and the shape memory spring 5 is provided commonly for at least two or more contacts 3, and has a structure that the shape memory spring 5 is long in the aligning direction of the contacts 3. Thus, there are advantages that the number of the shape memory springs 5 is remarkably reduced, and the spring force of the shape memory spring 5 applied to the contacts 3 becomes constant. This modified example is shown in Fig. 8. Fig. 8 shows only the shape memory spring 5, in which the other portions thereof are constructed the same as those of the first embodiment shown in Fig. 1, and detailed description of the modified example will be omitted.

The shape memory spring 5 of the applied modified example in Fig. 8 is common for at least two or more contacts 3, and has a structure that the shape memory spring 5 is long in the aligning direction of the contacts 3. Further, the surface of the shape memory spring 5 is covered with an insulating film 41 to be described later. Here, a method of covering the surface of the shape memory spring 5 with the insulating film 41 may spray, for example, fluorine powder paint or epoxy resin powder paint on the surface of the shape memory spring 5 by electrostatic painting and then baking the paint. To the shape memory spring 5 the insulating material such as polyimide resin, polyester resin, fluorine resin or vinyl resin may be extruded to be covered, or the surface of the shape memory spring 5 is covered by bonding an adhesive such as silicon bond to the inner surface of the film or glass cloth made of the above-mentioned resin. The adhesive may use, in addition to the silicon bond, rubber bond such as SBR (Styrene-butadiene rubber), NBR (Nitrile-butadiene rubber) or resin bond such as epoxy-urethane.

In the modified example in Fig. 8, all the surface of

the shape memory spring 5 is covered with the insulating film 41. However, only the portion to be contacted with the contacts 3 may be covered with an insulating film 41 as shown in Fig. 9. Or, covered is the portion to be contacted with the shape memory spring 5 of the contact 3 side, though not shown, with the insulating film 41 by various methods as described above.

In the embodiment as described above, the shape memory spring 5 is formed in the structure that is common for the contacts 3 to be long in the aligning direction of the contacts 3 and the shape memory spring 5 and the contacts 3 are insulated therebetween. Therefore, the spring force generated by the shape recovery of the shape memory springs 5 to be applied to the contacts 3 can be aligned constantly. Further, the number of parts can be remarkably reduced. In addition, when such an electronic connector is associated, since the shape memory spring 5 is common for a plurality of contacts 3, there is an advantage that the shape memory spring 5 is slid from one end to the other of the connector to be inserted.

A second embodiment of an electronic connector of the invention is shown in Fig. 10. This second embodiment has such features that a shape memory spring 5 used commonly for at least two or more contacts 3 and having a structure that is long in the aligning direction of the contacts 3 is disposed at the center of two rows of contacts 3 to simultaneously drive the contacts 3 of both the rows by the shape memory spring 5. In the second embodiment as shown in Fig. 10, two rows of a plurality of contacts 3 are associated, and U-shaped sectional configuration memory spring 5 is disposed at the center of the two rows of the contacts 3. The shape memory spring 5 is inserted at both edge thereof into shape memory spring holding portions 3D formed on the ways of the contacts 3 to be connected with the contacts 3. Here, reference numeral 41 designates an insulating film formed on a contacting portion of the shape memory spring 5 with the contacts 3 to insulate the contacts from the shape memory spring 5 in the same manner as that in Fig. 9. Reference numeral 20 denotes a partition wall for insulating the adjacent contacts 3 of the rows to project from the connector housing 1. An attitude holder 42 is placed in a recess of the shape memory spring 5 to stabilize the attitude of the shape memory spring 5 to transmit balanced spring force to the contacts 3 of both sides. The attitude holder 42 is supported by the side of the connector housing 1. In this second embodiment, the transformation temperature of the shape memory spring 5 is set to 80°C. The operation of the shape memory spring 5 of this case will be described with reference to Figs. 11 and 12. As shown in Fig. 11, the spring force of both the contacts 3 overcomes that of the shape memory spring 5 at ambient temperature time so that both the contacts 3 are opened at their interval. At this time, the opposite contact 10 can be inserted or removed without inserting force or removing force. When the shape memory spring 5 is then heated by the heater 7 to set the temperature to 80°C or higher, the shape memory spring 5 tends to recover

the shape stored in advance as shown in Fig. 12 (in this case, the shape closed at both edges of the U-shape) to pull both the contacts 3 of both sides inward, with the result that the contacting portions 3B of the contacts 3 are contacted by a predetermined contacting pressure with the opposite contact 10.

According to the second embodiment of the invention constructed as described above, the contacts 3 of the two rows at both sides of the shape memory spring 5 disposed at the center can be simultaneously driven, thereby reducing the number of the shape memory spring 5.

Fig. 13 shows a third embodiment of an electronic connector of the invention. The electronic connector of this third embodiment has a connector housing 1 made of an insulating material, and the connector housing 1 has a contact containing chamber 2 opened at the front surface of the connector housing 1. A plurality of contacts 3 are contained to be in oppositely aligned state in the contact containing chamber 2 in such a manner that the legs 3B of the contacts 3 pass externally through the connector housing 1 from the bottom. A driving chamber 4 is formed in the connector housing 1 adjacent to the ends of the contacts 3, and U-shaped or V-shaped shape memory spring 5 is positioned by a positioning projection 6 to be contained in the driving chamber 4. The positioning projection 6 is projected from the connector housing 1. The driving chamber 4 communicates with the contact containing chamber 2 via a guide 8 having an opening or a slit. A T-shaped operation transmitting member 9 for transmitting a recovery force generated when the shape memory spring 5 is recovered to the shape stored in advance when the temperature of the shape memory spring 5 is heated to the transformation temperature or higher is interposed between the shape memory spring 5 and the contact 3. The operation transmitting member 9 passes the guide 8 to be restricted in its moving direction by the guide 8, i.e., to be restricted to transmit the force in a normal direction to the contact 3.

This third embodiment is an optimum example as an electronic connector used at burn-in testing time for applying a temperature load as a reliability tester for electronic parts or mounting substrates. In this third embodiment, the shape memory spring 5 made, for example, of Ni-Ti alloy is set to 100°C of its transformation temperature. Therefore, in this embodiment of the electronic connector, the shape memory spring 5 is martensitic phase at ambient temperature to be soft and to be apparently readily plastically deformed so that the spring force of the contact 3 overcomes that of the shape memory spring 5 as shown in the left side in Fig. 13. In other words, the contact 3 presses the operation transmitting member 9 by its spring force to the driving chamber 4 side, and the contact 3 becomes an attitude that is displaced to the inner wall of the contact containing chamber 2. Therefore, the opposite contact 10 can be inserted or removed without inserting force or removing force in this state. Then, when the embodiment of this electronic connector is

inserted into the burn-in tester in the state that the opposite contact 10 is inserted and the testing atmosphere reaches becomes 100°C or higher, the shape memory spring 5 in the austenitic phase tends to recover the shape stored in advance, thereby overcoming the spring force of the contact 3 by the recovery force generated in this case to press the operation transmitting member 9 in the restriction in the direction of the guide 8 as shown in the right side of Fig. 13. Thus, the contact 3 is passes to the center of the contact containing chamber 2. Therefore, the contact 3 is pressed by the constant spring force by the opposite contact 10.

In the third embodiment described above, the shape memory spring 5 and the operation transmitting member 9 may be individually provided corresponding to the contacts 3. In this case, the operation transmitting member 9 may be formed of an electrically conductive material.

However, it is preferable that the number of the parts is reduced to simplify the structure and is constructed in a structure that the shape memory spring 5 is used commonly for at least two or more contacts 3 to stabilize the operation and is long in the aligning direction of the contacts 3. In this case, the operation transmitting member 9 is indispensably composed of an insulating material as in the third embodiment described above. Further, this feature is true for all the following embodiment to be described later. Additionally, in the third embodiment described above, a plurality of contacts 3 have been arranged in two rows in an aligned state. However, this third embodiment can also be applied to the case of one row of contacts at one side. This feature is also applicable to all the following embodiments.

Fig. 14 shows a fourth embodiment of an electronic connector of the invention. Since this fourth embodiment has a symmetry to the right and left sides, the left side will be omitted. Even in this fourth embodiment, a driving chamber 4 which communicates with a contact containing chamber 2 is formed in a connector housing 1 adjacent to the end side of each contact 3. The driving chamber 4 contains a U-shaped or V-shaped shape memory spring 5 commonly for at least two or more contacts 3, i.e., having a structure that is long in the aligning direction of the contacts 3. Here, the shape memory spring 5 is buried at its one end in the operation transmitting member 9 to be connected, and is inserted, for example, press-fitted at its other end into a groove 11 formed on the connector housing 1 to be connected to the connector housing 1. Thus, since the shape memory spring 5 is press-fitted at its other end into the groove 11 of the connector housing 1, the supporting end at operating time is fixed to reliably transmit the force of the shape memory spring 5 to the contact 3. When the groove 11 is continuously formed longitudinally of the connector housing 1, there is an advantage that, after all the contacts 3 are associated in the connector housing 1, the shape memory spring 5 connected with the operation transmitting member 9 is slid from one end of the connector to be mounted.

In the fourth embodiment described above, when

the atmospheric temperature is lower than the transformation temperature of the shape memory spring 5, the spring force of the contact 3 overcomes that of the shape memory spring 5 to press the shape memory spring 5 to the wall side of the driving chamber 4. In other words, the contact 3 becomes the state that is displaced to the wall side of the contact containing chamber 2, and hence the opposite contact 10 can be inserted in the state of noninserting force. When the atmospheric temperature thereafter reaches the transformation temperature or higher of the shape memory spring 5, the shape memory spring 5 tends to recover the shape stored in advance to transmit the recovery force generated in this case through the operation transmitting member 9 to the contact 3, while being supported at its one end by the groove 11, with the result that the contact 3 is pressed to the center of the contact containing chamber 2 to cause the contacting portion 3B of the contact 3 to press the opposite contact 10 by a predetermined contacting pressure. In this fourth embodiment, when the shape memory spring 5 and the operation transmitting member 9 are used commonly for at least two or more contacts 3, the operation transmitting member 9 serves as an insulating member of the contacts 3 and also serves as a member for transmitting the spring force of the shape memory spring 5 stably to the contact 3.

In Fig. 14, the operation transmitting member 9 and the shape memory spring 5 may be connected by providing a groove to which one end of the shape memory spring 5 is inserted on the operation transmitting member 9 and press-fitting one end of the shape memory spring 5 to the groove as the connection of the shape memory spring 5 with the connector housing 1.

When the operation transmitting member 9 is, for example, formed of thermoplastic resin, one end of the shape memory spring 5 is inserted to the groove formed on the operation transmitting member 9, and the groove of the operation transmitting member 9 made of the thermoplastic resin is thermally calked to be fixed. Thus, the connection of the shape memory spring 5 with the operation transmitting member 9 can be more reliably executed.

When one end of the shape memory spring 5 is inserted to the groove 11 formed on the connector housing 1, the width of the groove 11 must be matched to the thickness 0.2 to 0.3 mm of the shape memory spring 5 so as to necessarily fix the shape memory spring 5 inserted to the groove 11, and the width of the groove must be very narrow. As a result, there arises a problem that the working of the groove 11 becomes very difficult. Even if the groove 11 is precisely formed, when the thin shape memory spring 5 is intended to be press-fitted unreasonably to the groove 11, there occurs a danger of deforming the shape memory spring 5 over the elastic limit in the worst case. Therefore, as shown in Fig. 15, a T-shaped mounting member 14 is, for example, mounted at one end of the shape memory spring 5 inserted to the groove 11. In this case, the shape of the groove 11 of the opposite side of mounting is naturally formed in T-shape. In Fig. 15, symbol 9A

designates a projection formed on the operation transmitting member 9 to thereby reliably transmit the force of the shape memory spring 5 to the contact 3.

Here, the mounting member 14 is mounted at one end of the shape memory spring 5, as shown, for example, in Fig. 16, by splitting the mounting member 14 into mounting member pieces 14A, 14B, inserting the projection 15 of one mounting member piece 14B through a cutout 16 of the shape memory spring 5 to engage it with the opening 17 of the opposite mounting member piece 14A to integrate them as shown in Fig. 17. In this case, the mounting member pieces 14A, 14B may be bonded by a bond as required. Further, the mounting member 14 may be formed by insert molding at the shape memory spring 5 by direct molding. Fig. 18 shows another example of a mounting member 14. In this case, the mounting member pieces 14 are partially formed at opposite sides.

When the mounting member 14 is provided at the shape memory spring 5 in this manner, the groove 11 of the connector housing 1 is increased in its width, with the result that the groove 11 can be readily formed. Since the shape memory spring 5 is mounted in the groove 11 through the mounting member 14, it is not necessary to forcibly press it to the groove as the conventional one, and can avoid the possibility of bending the shape memory spring 5 over the criterion. As shown in Fig. 15, when the section of the mounting member 14 is formed, for example, in T-shape, there is an advantage that the shape memory spring 5 is prevented from being removed from the groove 11. In Fig. 15, the groove 11 of the connector housing 1 side has been merely described. However, even when the shape memory spring 5 is inserted into the groove formed on the operation transmitting member 9, the above method may be also applied.

Fig. 19 shows a fifth embodiment of an electronic connector of the invention. The feature of this fifth embodiment is different from the third embodiment in Fig. 13 in that the contact 3 and the operation transmitting member 9 are connected. Here, reference numeral 6 designates a positioning projection for reversely hanging and positioning a U-shaped or V-shaped shape memory spring 5 to be projected from a connector housing 1. Numeral 7 denotes a heater for heating a shape memory spring 5. The force of the shape memory spring 5 is restricted in its direction by a guide 8 having an opening or a slit through an L-shaped operation transmitting member 9 connected to a contact 3 to be reliably transmitted to the contact 3. In this fifth embodiment, the transformation temperature of the shape memory spring 5 is set to 80°C. When the shape memory spring 5 is heated by the heater 7 to 80°C or higher, the shape memory spring 5 in the austenitic phase tends to recover the shape stored in advance, thereby overcoming the spring force of the contact 3 to become the state of the right side in Fig. 19. More specifically, the operation transmitting member 9 is pulled by the force of the shape memory spring 5 in a direction restricted by a guide 8 into a driving chamber 4, thereby pulling the

contact 3 to the driving chamber 4 side. Accordingly, the opposite contact 10 can be inserted or removed without inserting or removing force in this state. Then, when the heater 7 is deenergized so that the temperature in the driving chamber 4 reaches ambient temperatures, the shape memory spring 5 becomes the martensitic phase to be soft and to be apparently readily plastically deformed. Thus, the spring force of the contact 3 overcomes that of the shape memory spring 5, the contact 3 is protruded to the center side of the contact containing chamber 2, and pressed by a predetermined spring contacting pressure to the opposite contact 10 inserted by the contacting portion 3B of the contact 3 into the contact containing chamber 2. Here, when the operation transmitting member 9 is formed of an insulating member such as plastic, the member 9 can be readily formed, and the shape memory spring 5 and the contact 3 can be reliably insulated.

Fig. 20 shows a sixth embodiment of an electronic connector of the invention. In the electronic connector of this sixth embodiment, a contact containing chamber 2 is opened at the front surface of a connector housing 1 made of an insulating material. A plurality of contacts 3 are associated in two rows in parallel longitudinally in the contact containing chamber 2. The contacts 3 of two rows are arranged so that the contacting portions 3B of the contacts 3 of the two rows are opposed to each other as pairs, and U-shaped or V-shaped sectional shape memory spring 5 is disposed to drive the contacts 3 between the contacts 3 of two rows. Further, the shape memory spring 5 is provided commonly for the contacts 3 of both side along the rows to be inserted at both side edges of the bent recess to grooves 12 formed on operation transmitting member 9 made of an insulating material to simultaneously transmit the tension to the contacts 3 of two rows through the operation transmitting member 9. The contacts 3 are partly buried to be connected, for example, in the operation transmitting member 9 at molding time, and formed in a structure that the operation transmitting member 9 is supported midway of the contacts 3. As means for burying the contacts 3 in the operation transmitting member 9 may use the above-mentioned molding or means for press-fitting the contacts 3 to openings formed in advance on the operation transmitting member 9. In this case, it is necessary to eliminate a play between the contact 3 and the operation transmitting member 9 to reliably transmit the force of the shape memory spring 5 to the contact 3. The material of the operation transmitting member 9 may, for example, preferably employ heat resistance resin having sufficient physical strength under using conditions such as polyphenylene sulfide, polyetherimide, etc. When a groove 12 for connecting the shape memory spring 5 to the operation transmitting member 9 is continuously formed from one end to the other end of the operation transmitting member 9, the contacts 3 are associated in the connector housing 1, the shape memory spring 5 is then preferably slid from one end to be mounted on the operation transmitting member 9. In this sixth embodiment, the shape memory spring 5 may be bonded by a bond to the

operation transmitting member 9 after inserting the shape memory spring 5 to the groove 12 of the operation transmitting member 9. The transformation temperature of the shape memory spring 5 of this sixth embodiment is set to 80°C. When the atmospheric temperature reaches 80°C or higher, the shape memory spring 5 the austenitic phase generates a large recovery force. The operation of this sixth embodiment is shown in Figs. 21 and 22. Fig. 21 shows the state of the shape memory spring 5 at ambient temperatures. In this state, the shape memory spring 5 is in the martensitic phase to be soft and to be apparently readily plastically deformed. The shape memory spring 5 is overcome by the spring force of the contact 3 to be opened outside by the spring force of the contact 3 through the operation transmitting member 9. In this state, the opposite contact 10 may be inserted or removed without inserting or removing force. Then, Fig. 22 shows the state that the atmospheric temperature becomes 80°C or higher and the shape memory spring 5 becomes the austenitic phase. In this case, the shape memory spring 5 is recovered to the shape stored in advance, i.e., recovered to the shape for closing at both U-shaped or V-shaped ends to pull the contacts 3 provided in two rows through the operation transmitting member 9 inside, thereby generating a predetermined contacting pressure by the contacting portion 3B of the contact 3 to the opposite contact 10.

This sixth embodiment is designed to obtain a contacting pressure at high temperature time. However, the shape memory spring 5 may be provided to insert or remove the opposite contact 10 without inserting or removing force by altering the memory shape of the shape memory spring 5 (e.g., by storing the shape opened at both ends of U-shape) to generate a predetermined contacting pressure due to the closure of the contact 3 in such a manner that the spring force of the contact 3 overcomes that of the shape memory spring 5 at ambient temperatures, and recovering the shape stored in the shape memory spring 5 at its transforming temperature or higher to open the shape memory spring 5 at the outside.

In the sixth embodiment described above, though the electronic connector has two rows of contacts 3, either one row of the contacts 3 may be omitted. In this case, the other end of the shape memory spring 5 is inserted to the groove 11 formed on the connector housing 1 as shown, for example, in Fig. 14 or 15.

In the sixth embodiment described above, a method of mounting the shape memory spring 5 in the groove 12 of the operation transmitting member 9 may employ a mounting member 14 as shown in Fig. 23. This is the application of the method shown in Fig. 15. Thus, the shape memory spring 5 may not remove from the groove 12 of the operation transmitting member 9, and there is no possibility that the inserting end of the shape memory spring 5 is excessively bent when inserted.

Fig. 24 shows a seventh embodiment of an electronic connector of the invention. This seventh embodiment is modified from the sixth embodiment



shown in Figs. 20 to 22. In the sixth embodiment, the operating ranges of the shape memory spring 5 and the contacts 3 are determined by the balance of the contacts 3 of the bias spring and the force of the shape memory spring 5 with the result that there is a problem that the contacts 3 cannot be accurately controlled in positioning. In other words, when considering the repetitive fatigue of the shape memory spring 5 and the contacts 3 and the long time restriction of predetermined deformation amount, it is necessary to accurately manage the strain amount and to use them in a range that the strain amount may not exceed a predetermined value. Thus, in Fig. 24, an inner wall 1A of a connector housing 1 for restricting the outward operation range of an operation transmitting member 9 is formed at one side of the operation transmitting member 9 driven by the shape memory spring 5 in the operating direction (lateral direction in Fig. 24), and a stopper member 13 is formed to restrict the operating range of the other inward direction. In the seventh embodiment described above, the stopper member 13 and partition walls 20 are connected by a connecting portion 13A as shown in Fig. 25 to be positioned and contained in a contact containing chamber 2. The stopper member 13, the connecting portion 13A and the partition wall 20 may be integrally formed with the connector housing 1, or the partition 20 is integrally formed with the connector housing 1, and the stopper member 13 may be directly connected to the longitudinal side of the connector housing 1. Figs. 26 and 27 are cross-sectional views showing the operation of the seventh embodiment. Fig. 26 shows the state, different from the case of Fig. 20, that of the case of the electronic connector at ambient temperature to be inserted into or removed from the opposite contact 10 without inserting or removing force at high temperature. In this state, the shape memory spring 5 in the martensitic phase is soft and apparently readily plastically deformed. Thus, force of the shape memory spring 5 is overcome by the spring force of the contact 3 to be inwardly pressed through the operation transmitting member 9. At this time, the operation transmitting member 9 is contacted with the stopper member 13 to stop moving inwardly. In Fig. 26, the opposite contact 10 is omitted. However, the contact 3 and the opposite contact 10 are contacted in this state. Then, when the heater 7 disposed between the connector housing 1 and the shape memory spring 5 is energized to heat the shape memory spring 5 to the transformation temperature or higher, the shape memory spring 5 is transformed to the austenitic phase to tend to recover the shape stored in advance (in this case, the shape opened at both side U-shaped ends is stored), thereby expanding the contacts 3 through the operation transmitting member 9 as shown in Fig. 27. At this time the operation transmitting member 9 is contacted with the inner wall 1A of the connector housing 1 to stop moving outward. Accordingly, even if the shape memory spring 5 generates spring force more than required at this time, a large strain is not applied to the contact 3. The opposite contact 10 not shown in this

state can be inserted or removed without inserting or removing force.

In the seventh embodiment described above, when the shape for closing both ends is stored in the shape memory spring 5 when the shape memory spring 5 reaches its transformation temperature or higher, the shape memory spring 5 can operate reversely as in the cases of Figs. 26 and 27.

In the seventh embodiment described above, either one row of contacts 3 may be omitted similarly to the case of the sixth embodiment. In this case, the other end of the shape memory spring 5 is inserted fixedly to a groove 11 formed on a connector housing 1 as shown, for example, in Figs. 14 and 15.

Fig. 28 shows an eighth embodiment of an electronic connector of the invention. This eighth embodiment is modified and improved from the sixth embodiment in Fig. 20 and the seventh embodiment in Fig. 24. More specifically, in the sixth embodiment, the shape memory spring 5 is exposed with high temperature atmosphere, takes several tens seconds to reaches its transformation temperature, and even a simple continuity check cannot be executed at the opposite contact 10 side during the period. In the seventh embodiment, even if the energization of the heater 7 is stopped, it takes a considerable time to generate a contacting pressure between the contacts 3 and the opposite contact 10 due to the narrow interval of the contacts at both sides aligned in two rows as shown in Fig. 26 until the temperature of the shape memory spring 5 falls below its transformation temperature. In this case, the continuity test cannot be performed as described above. In other words, in the above-mentioned embodiments, it takes several tens seconds to transform the shape memory spring 5, and there is a problem that even a simple initial check cannot be executed during the period. Therefore, the eighth embodiment has a feature that an initial check such as a continuity check can be executed during the period until the shape memory spring 5 is transformed to the desired phase. In this eighth embodiment as shown in Fig. 28, the contacts 3 have weak spring force auxiliary contacting portions 3E which stand by at positions to contact before a strong spring force main contacting portion 3B contacts the opposite contact 10. This weak spring force auxiliary contacting portion 3E is formed with a narrow auxiliary spring portion 24 so that a slit 23 is formed from the upper portion toward the lower portion to become a weak spring force as shown in Fig. 29, and the auxiliary spring portion 24 is extended to the center of the contact containing chamber 2 as shown in Fig. 28.

In the electronic connector of the eighth embodiment described above, when the shape memory spring 5 becomes, for example, the martensitic phase, the weak spring force auxiliary contacting portion 3E is extended inward to stand by. Accordingly, the opposite contact 10 can contact the weak spring force auxiliary contacting portion 3E before contacting the strong force main contacting portion 3B, and even if the shape memory spring 5 is not transformed to the austenitic phase, i.e., is not heated, the initial check can be executed. When the

shape memory spring 5 is heated to be transformed to the austenitic phase, the contact 3 is moved to the center of the contact containing chamber 2 through the operation transmitting member 9 by the force of the shape memory spring 5, and the strong spring force main contacting portion 3B is contacted with the opposite contact 10. More particularly, in Fig. 28, the shape memory spring 5 is the martensitic phase at ambient temperature, and is stopped in balance with the contact 3. Since the strong spring force main contacting portion 3B is disposed steadily at the position slightly retreated with respect to the opposite contact 10 from the weak spring force auxiliary contacting portion 3E at this time, only the weak spring force auxiliary contacting portion 3E is contacted when the opposite contact 10 is inserted. Thus, the opposite contact 10 can be inserted with extremely weak force. The necessary minimum contacting pressure is generated for an initial check at this time. After the initial check is completed, when the shape memory spring 5 arrives at high temperature of using state, the shape memory spring 5 is transformed to the austenitic phase, becoming the stored shape, i.e., the state as shown by broken lines in Fig. 28. As a result, the strong spring force main contacting portion 3B is contacted with the opposite contact 10 by large contacting pressure, and high reliability is obtained even in the continuous usage at high temperature. When returned again to ambient temperature, the shape memory spring 5 is stopped at the position designated by solid lines in Fig. 28, and the opposite contact 10 and the contact 3 are contacted only at the weak spring force auxiliary contacting portion 3E.

Even in case of an electronic connector used at ambient temperature, when this contact 3 is applied, the initial check can be executed immediately after the heater 7 is deenergized, and a high contacting pressure is obtained when the temperature falls below the transformation temperature of the shape memory spring 5.

Fig. 30 shows another modified example of this eighth embodiment. The contact 3 is different from that in Fig. 29, a slit 23 is formed from the upper portion to the lower portion of the contact 3 to form an auxiliary spring portion 24. Thus, a weak spring force auxiliary contacting portion 3E is stopped at a predetermined position substantially irrespective of the movement of the strong spring force main contacting portion 3B driven by the shape memory spring 5 different from that in Fig. 17. An example of using the contact 3 is shown in Figs. 31 and 32. This electronic connector is used at ambient temperature. In this example, the outwardly pulling force of the shape memory spring 5 in the austenitic state heated by the heater 7 as shown in Fig. 31 is transmitted through the operation transmitting member 9 to the contact 3, and the strong spring force main contacting portion 3B of the contact 3 is pulled to the inner wall side of the connector housing 1. In this state, only the weak spring force auxiliary contacting portion 3E remains at the center of the contact containing chamber 2 to stand by. Accordingly, the opposite contact 10 is contacted with the

weak spring force auxiliary contacting portion 3E by weak contacting pressure. Therefore, an initial, check can be executed by the weak spring force auxiliary contact 3E during several tens seconds before the heater 7 is stopped and the shape memory spring 5 is returned to the martensitic phase. After the several tens second, the shape memory spring 5 is returned to the martensitic state. Then, as shown in Fig. 32, the spring force of the contact 3 overcomes the spring force of the shape memory spring 5 to return to the center of the contact containing chamber 2, with the result that the contacting pressure of the strong spring force main contacting portion 3B is added to the contacting pressure of the weak spring tension auxiliary contacting portion 3E to act a large contacting pressure on the opposite contact 10.

Figs. 33 to 37 show a ninth embodiment of an electronic connector of the invention. The eighth embodiment in Fig. 28 forms the auxiliary spring portion 24 by forming the slit 23 on the contact 3, while the ninth embodiment is improved to provide the same advantages as those in the eighth embodiment by one contact 3. The portions except the contact 3 are constructed fundamentally the same as the sixth embodiment in Fig. 20, and only the feature of the ninth embodiment will be shown and described. In the ninth embodiment, the contact 3 is composed of a contact weak spring portion 3F erected from the bottom of a connector housing 1 in a contact containing chamber 2 so that the upper end side is bent in a predetermined radius of curvature downward, and a contact strong spring portion 3G formed continuously at the end of the contact weak spring portion 3F to be bent in V-shape. The contacting portion 3B is formed at a boundary between the contact weak spring portion 3F and the contact strong spring portion 3G. A blocklike operation transmitting member 9 is formed on the way of the contact weak spring portion 3F corresponding to the contact strong spring portion 3G. One end of the shape memory spring 5 is press-fitted to the groove 12 of the operation transmitting member 9. An engaging bent portion 3K is formed substantially perpendicularly bent at the end of the contact strong spring portion 3G. The engaging bent portion 3K is placed on the upper surface of the operation transmitting member 9.

In the electronic connector of the ninth embodiment described above, when the atmosphere is in ambient temperature and the shape memory spring 5 is in the martensitic state, the contacting portion 3B is disposed steadily at a position contacted when the opposite contact 10 is inserted as shown in Fig. 33. In this state, the spring force of the contact weak spring portion 3F of the black solid portion in Fig. 35 at load acting point 3H is balanced with the force of the shape memory spring 5. Then, when the opposite contact 10 is inserted as shown in Fig. 36, the contacting portion 3B is pressed back to the surface line of the opposite contact 10 to generate a predetermined weak contacting pressure to become the state that an initial check can be executed. At this time, the spring force of the contact 3 affecting the contacting pressure is

generated at the portion of the contact weak spring portion 3F of black solid portion in Fig. 36. The stiffness at this time is that generated by the contact weak spring portion 3F to be very weak as compared with that of the state of Fig. 37 to be described later, and even if the position of the contacting portion 3B is slightly displaced, the contacting pressure does not alter to a greater extent.

When the electronic connector of this ninth embodiment is exposed to the high temperature of using state, i.e., the transformation temperature or higher of the shape memory spring 5 after the opposite contact 10 is inserted, the shape memory spring 5 in the austenitic phase overcomes the spring force of the contact 3, and to tend to recover to the stored shape, thereby stopping steadily in the state in Fig. 34. As a result, the contacting point 3B is contacted with the opposite contact 10 by large contacting pressure to obtain a high reliability in the continuous operation at high temperature. At this time, the spring force of the contact 3 affecting the contacting pressure is initially generated by the contact weak spring portion 3F of black solid portion in Fig. 36, but as the shape memory spring 5 is recovered in its shape, the spring force of the contact 3 is generated from when the operation transmitting member 9 is contacted with the oblique surface of the contact strong spring portion 3G in both the black solid portion and in the hatched portion in Fig. 37. The load acting point at this time becomes two points of 3H and 3M in Fig. 37, and particularly the black solid portion provides large stiffness of the contact strong spring portion 3G, and the shape recovering force of the shape memory spring 5 is transmitted to the contacting portion 3B substantially as it is.

In the electronic connector of this ninth embodiment of this type, it is preferable not to deform the contact 3 as low as possible, i.e., to increase the stiffness so as to utilize the force of the shape memory spring 5 as the contacting pressure, but when it is, on the contrary, necessary to contact the opposite contact 10 with the contact 3 by weak spring force for the purpose of initial check, the stiffness of the contact 3 is preferably smaller. In the ninth embodiment, this requirement is satisfied by altering the stiffness at the load acting point of the contact 3 during the period while the operations of the contact 3 and the shape memory spring 5 have been completed upon rising of the temperature after the opposite contact 10 is inserted.

The opposite contact 10 is wiped on the surface by the contacting portion 3B of the contact 3 when the opposite contact 10 is initially inserted, but in this ninth embodiment, the contacting point of the contacting portion 3B and the opposite contact 10 is not altered always thoroughly during a series of operations of the contact 3 and the shape memory spring 5 described above. Therefore, the contact of extremely high reliability is obtained from the electric point of view.

When using at ambient temperature, the transformation temperature of the shape memory spring 5 is set to low temperature such as 0°C, and when the opposite contact 10 is inserted, the electronic

connector is cooled. Then, the similar effects to those described above are obtained. In the ninth embodiment described above, this can be applied to both one and two rows of the contacts 3 in the same manner as the embodiment described above.

According to the ninth embodiment described above, different from the eighth embodiment, the contact 3 is composed of the contact weak spring portion 3F and the contact strong spring portion 3G, the contacting portion 3B is formed at the boundary between both the spring portions, the memory recovery force of the shape memory spring 5 is acted through the operation transmitting member 9 to the contact strong spring portion 3G, and the contacting portion 3B is disposed at the position capable of contacting when the opposite contact 10 is inserted in the stand-by state. Therefore, the contacting portion 3B extended to the inserting passage of the opposite contact 10 is supported by the contact weak spring portion 3F at the initial check time by contacting the opposite contact 10 with the contact 3, there is an advantage that it moved by the weak force when pressed so that the initial check can be executed by extremely weak inserting or removing force. When the shape memory spring 5 is operated, the force of the shape memory spring 5 is acted through the operation transmitting member 9 to the contact strong spring portion 3G of the contact 3. Thus, the attenuation of the force of the shape memory spring 5 is minimized to transmit the force of the shape memory spring 5 to the contacting portion 3B to obtain a necessary contacting pressure different from the contact weak spring portion 3F. Further, different from the embodiments described above, this ninth embodiment has an advantage that the surface of the opposite contact 10 is wiped when the opposite contact 10 is inserted.

Figs. 38 to 40 show a tenth embodiment of an electronic connector of the invention. This tenth embodiment is improved to accurately manage the position of the operating range of the contact 3 in the ninth embodiment for the purpose of improving fatigue characteristics by eliminating the strain of the contact 3 exceeding a predetermined amount.

In the tenth embodiment, the electronic connector has a symmetry at right and left sides, and left half will be omitted for the clarity of the drawings and the description. Since the essential portion of the tenth embodiment is substantially the same as that of the ninth embodiment in Figs. 33 to 37, the description of the same portions will be omitted.

In Figs. 38 to 40, a first restricting portion 30 made of a projection for restricting the operating range of the contact 3 is formed on the side of the folded portion 3N of the contact weak spring portion 3F of the contact 3. A second restricting portion 31 made of a recess for restricting the operating range of the contact 3 in cooperation with the first restricting portion 30 is formed correspondingly on the partition wall 20 between the contacts 3 of the rows. The first and second restricting portions 30, 31 contact with one another to restrict the operating range of the contact 3.

In the electronic connector of the tenth embodi-

ment described above, when the opposite contact 10 is inserted at ambient temperature, the first restricting portion 30 stops at the stopper 31B of the second restricting portion 31 to always exert a predetermined contacting pressure. The shape memory spring 5 is recovered in the shape in a direction that the shape memory spring 5 is contracted inward at high temperature time, i.e., at the transformation temperature or higher of the shape memory spring 5. In this case, even if the shape memory spring 5 produces the force more than required, the contact 3 is contacted at the first restricting portion 30 with the stopper 31A of the second restricting portion 31 to be restricted. Thus, the contact 3 does not exceed the critical strain.

Figs. 41 and 42 show an applied example of the tenth embodiment. This applied example is different from the tenth embodiment in that a first restricting portion is formed with a recess and used at both ends as stoppers 30A, 30B and a second restricting portion 31 is formed with a projection.

In the electronic connector of the applied example of the tenth embodiment described above, the contact 3 overcomes the spring force of the shape memory spring 5 at ambient temperature to tend to open outward, but the stopper 30A contacts the second restricting portion 31 to stop, thereby becoming a predetermined contacting pressure when the opposite contact 10 is inserted. When the atmospheric temperature rises to the transformation temperature or higher of the shape memory spring 5 so that the spring force of the shape memory spring 5 overcomes the spring force of the contact 3 to cause the shape memory spring to recover in the shape in an inwardly contracting direction, even if the opposite contact 10 is not inserted, the stopper 30B of the first restricting portion 30 formed on the contact 3 is stopped by the second restricting portion 31 formed on the partition wall 20 to inhibit to exceed the critical strain of the contact 3. When there is a facing contact 3, i.e., when the contacts 3 are opposite in two rows, it prevents the facing contacts 3 from contacting with one another. In the tenth embodiment, the electronic connector has been used at the high temperature. However, in case of the electronic connector used at ambient temperature, the transformation temperature of the shape memory spring 5 is set, for example, to 0°C, the electronic connector is cooled when the opposite contact 10 is inserted, and it may be exposed with the ambient temperature when the opposite contact 10 is inserted. Or, a heater is associated in the contact containing chamber 2 of the connector housing 1, and when the opposite contact 10 is inserted, the heater is energized, and the contact 3 is opened outside by the shape memory spring 5 for storing in advance the shape to open both ends of its U-shaped portion to insert or remove the opposite contact 10 without inserting or removing force, and when the energization of the heater is stopped after the opposite contact 10 is inserted, sufficient contacting pressure can be obtained at ambient temperature.

Fig. 43 shows an eleventh embodiment of an electronic connector of the invention. In the eleventh

embodiment, in the electronic connector of the type that U-shaped open edges of a shape memory spring 5 are press-fitted to grooves 12 formed on an operation transmitting member 9, it is devised that the shape memory spring 5 is not removed from the groove 12 of the operation transmitting member 9. In other words, an elastic member 35 is provided between the shape memory spring 5 and the connector housing 1, and the shape memory spring 5 is energized by the elastic member 35 in a direction of the groove 12 of the operation transmitting member 9. As a result, there are advantages that the shape memory spring 5 is prevented from removing from the groove 12 of the operation transmitting member 9 and the operating point of the shape memory spring 5 is stabilized. When the elastic member 35 is mounted in the structure where no heater 7 is provided in the electronic connector of the structure in Fig. 31, the elastic member 35 is inserted between the shape memory spring 5 contained in the driving chamber 4 and the bottom of the driving chamber 4, and the shape memory spring 5 is pressed by the elastic member 35 to the groove 12.

According to the electronic connector constructed as described above in accordance with the invention, it is appreciated that the opposite contact can be inserted or removed without or with low inserting or removing force. The electronic connector of the invention provides simple structure and high reliability as compared with the conventional one. Further, an initial check can be executed as required.

## Claims

### 1. An electronic connector comprising:

a plurality of contacts associated in one or more rows in a connector housing, and  
a shape memory spring associated in the connector housing for driving the contacts, the shape memory spring transmitting a recovery force generated when the shape memory spring reaches its transformation temperature or higher to the contacts while recovering the shape stored when the shape memory spring reaches its transformation temperature or higher to the contacts while recovering the shape stored when the shape memory spring reaches its transformation temperature or higher and returning to the shape before the shape memory recovery by the spring force of the contact when the shape memory spring falls below its transformation temperature.

2. The electronic connector according to claim 1, wherein said shape memory springs are provided respectively individually provided at the contacts.

3. The electronic connector according to any of claims 1 and 2, wherein at least one end of said shape memory spring is held by a shape memory spring holding portion provided on the way of the contact to be connected to the

contact.

4. The electronic connector according to any of claims 1 to 3, wherein said shape memory spring and said contact are insulated by an insulating material, and said shape memory spring has a structure that is used commonly for at least two or more contacts and is long in the aligning direction of said contacts.

5. The electronic connector according to any of claims 1 to 4, wherein said insulating material is an operation transmitting member interposed between said contact and said shape memory spring for transmitting the force of said shape memory spring to the contact, said operation transmitting member transmitting the recovery force generated when said shape memory spring reaches its transformation temperature or higher to the contact while recovering the stored shaped when said shape memory spring reaches the transformation temperature or higher.

6. The electronic connector according to any of claims 1, 2, 4 and 5, wherein said shape memory spring and said operation transmitting member are buried at its one end of said shape memory spring in said operation transmitting member to be connected, and said shape memory spring and said connector housing are connected by inserting the other end of said shape memory spring to a groove formed on the connector housing.

7. The electronic connector according to claim 5, wherein said shape memory spring and said operation transmitting member are inserted at its one end of said shape memory spring in the groove of said operation transmitting member to be connected, and said shape memory spring and said connector housing are connected by inserting the other end of said shape memory spring to a groove formed on the connector housing.

8. The electronic connector according to any of claims 5 and 7, wherein said shape memory spring and said operation transmitting member are buried at its one end of said shape memory spring in said operation transmitting member to be connected, and said shape memory spring and said connector housing are connected by inserting a mounting member having at the other end of said shape memory spring to a groove formed on the connector housing.

9. The electronic connector according to claim 5, wherein said operation transmitting member is connected to said contact.

10. The electronic connector according to any of claims 5 and 9, wherein said operation transmitting member and said contact are buried at a part of said contact in said operation transmitting member to be connected, and said operation transmitting member and said shape memory spring are connected by inserting the part of said shape memory spring to a groove formed on the operation transmitting member.

11. The electronic connector according to any of claims 5 and 10, wherein said shape memory

spring is connected by inserting a mounting member having at the end into a groove formed on said operation transmitting member.

12. The electronic connector according to claim 10, wherein an inner wall of said connector housing is formed for restricting the operating range of said operation transmitting member in one direction at one side of the operation transmitting member in the operating direction of the operation transmitting member, and a stopper member for restricting the operating range of said operation transmitting member in the other direction is formed part from and at the other side of said operation transmitting member in the operating direction of the operation transmitting member.

13. The electronic connector according to claim 1, wherein said contact has a strong spring force main contacting portion contacted with the opposite contact and a weak spring force auxiliary contacting portion standing by at a position capable of contacting before the strong spring force main contacting portion is contacted with the opposite contact.

14. The electronic connector according to claim 1, wherein said contact has a contacting portion contacted with the opposite contact, a contact weak spring portion supported in a cantilever to said connector housing and so positioned as to exist at a position contacting at the time of inserting opposite contact at the contacting portion, and a contact strong spring portion provided integrally with the end of the contact weak spring portion.

15. The electronic connector according to any of claims 8 and 14, wherein said contact has a first restricting portion for restricting the operating range of the contact, a second restricting portion for restricting the operating range of the contact in cooperation with the first restricting portion at a partition wall between the contacts, and said first and second restricting portions are engaged in such a manner that one is a recess and the other is a projection.

16. The electronic connector according to claim 5, wherein the shape of said shape memory spring is U or V shape, and an elastic material for energizing one end of said shape memory spring inserted to the groove of the operation transmitting member in a direction for pressing the one end of the shape memory spring into the groove of the operation transmitting member is interposed between the folded portion of the shape memory spring and the connector housing.

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 10




FIG. 9




FIG. 11




FIG. 12




FIG. 13




FIG. 14






FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 26




FIG. 25




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 38




FIG. 39




FIG. 40




FIG. 42




FIG. 43




FIG. 41

